AMENDMENTS TO THE CLAIMS

This listing of claims replaces all prior versions of claims in the application.

LISTING OF THE CLAIMS:

Claim 1 (Currently Amended): A two-way DC-DC converter comprising: a terminal for

a low-voltage side; a terminal for a high-voltage side; a transformer including a winding wire for

the low-voltage side and a winding wire for the high-voltage side; a switching section for the

low-voltage side inserted between the terminal for the low-voltage side and the winding wire for

the low-voltage side; a switching section for the high-voltage side inserted between the terminal

for the high-voltage side and the winding wire for the high-voltage side; a rectifying element for

the low-voltage side connected in parallel with switching elements in the switching section for

the low-voltage side; a rectifying element for the high-voltage side connected in parallel with

switching elements in the switching section for the high-voltage side; and a control circuit which

controls switching elements in the switching section for the low-voltage side and switching

elements in the switching section for the high-voltage side, wherein

an LC resonant circuit is provided between the winding wire for the high-voltage side and

the switching section for the higher voltage side, or between the winding wire for the low-voltage

side and the switching section for the lower voltage side, which causes the current flowing on the

winding wire of the low and high voltage sides to have sinusoidal waveforms.

Page 2

Response under 37 CFR 1.111 Serial No. 10/781,699 Attorney Docket No. 042115

Claim 2 (Original): The two-way DC-DC converter according to claim 1, wherein the LC resonant circuit is provided between the winding wire for the high-voltage side and the switching section for the higher voltage side.

Claim 3 (Original): The two-way DC-DC converter according to claim 1, wherein both of the switching section for the lower voltage side and the switching section for the higher voltage side have a configuration in which four switching elements are bridged.